

GAP-145F-S7-SOLO Series 1U RUGGED SERVER



3rd Gen Intel® Xeon® Scalable Processors
Front I/O - Rear Power Supply



GAP is a family of rugged servers and workstations with an aluminum construction, designed for applications that require robust and qualified MIL-GRADE equipment, suitable for operations in critical environments.

GAP-145F-S7-SOLO rugged servers feature single socket 3rd Gen Intel® Xeon® Scalable Processors (Ice Lake), a balanced architecture that delivers built-in AI acceleration and advanced security capabilities, up to 2TB DDR4-3200 RAM and 64 lane PCIe Gen 4. The integrated IPMI services support monitoring, control, and management functions sending alarm notifications in case of critical events.

GAP-145F-S7-SOLO are designed for 19" rackmounting and have a 1U chassis with a depth of 450mm.

The front I/O and rear power supply layout includes an internal M.2 NVMe sockets and a 3.5" drive bay that can host up to two removable U.2 NVMe SSD or up to three removable 2.5" SAS/ SATA SSD.

GAP-145F-S7-SOLO rugged servers host up to two Full Height Full Length PCIe cards and one Low Profile one.

Additional boards can be provided with a dedicated retainer kit for an optimal protection against shocks and vibrations also during transport.

GAP servers are designed to meet MIL-STD-810F for temperature and shocks, MIL-STD-167-1A for vibrations. Optionally, they can conform to MIL-STD-461 for EMI / EMC.

The I/O connectors and the power supply input can be provided with MIL-GRADE connectors upon request.

All units are delivered with their inventory list to ensure configuration control and reproducibility over time. Upon request, all server configurations can run specific thermal or mechanical environmental stress test.

FEATURES

- 1U Rugged Server - 450mm depth
- Single Socket Motherboard
- 3rd Gen Intel® Xeon® Scalable Processors
- Front I/O connectors and rear Power Input
- Single AC or DC Power Supply
- Removable Fans
- DVD
- 2x U.2 NVMe or 3x 2.5" SATA/SAS SSD
- Up to 3 PCIe boards
- Optional Conformal Coating
- MIL-STD-810G
- Optional MIL-STD-461

Technical Specifications

System

CPU	3 rd Gen Intel® Xeon® Scalable processors Single Socket LGA-4189 (Socket P+) max 205W TDP
Memory	Up to 2TB ECC RDIMM, DDR4-3200MHz; 8 DIMM slots
Chipset	Intel® C621A
Graphics	ASPEED AST2600 BMC
Network Connectivity	1x Dedicated IPMI LAN port 2x 10 GbE ports
Storage	Internal: 1x M.2 NVMe; M-Key, 2280/22110 2x Disk on Module Removable: Up to 2x U.2 NVMe SSD or Up to 3x 2.5" SATA / SAS SSD
TPM	1x TPM Header
Motherboard I/O shield	Available on the front: 1x COM; 1x IPMI LAN; 2x USB 2.0; 2x USB 3.2; 2x GbE; 1x VGA
Expansion slots	2x PCI-E 4.0 x16 slot FHFL 1x PCI-E 4.0 x16 slot (Low profile)
Operative Systems	Windows® 10 IoT Enterprise 64bit, Windows® Server 2016 64bit; Windows® Server 2019 64bit; RHEL 8.4 64bit; Ubuntu 20.04.2 LTS SVR 64bit; CentOS 7.9 64bit
IPMI	IPMI2.0, SPM, Watchdog; SNMP and e-mail alarms and notifications
Remote Monitoring	Monitoring, control, and management functions (fan speed, temperature, voltage, redundant power failure, power consumption, disk health, raid health, and memory health)

Power Supply

Power Supply	AC single Power Supply DC Single Power Supply
---------------------	--

Mechanical

Dimensions	483 x 44 x 450 mm (W x H x D)
Material	Aluminum with surface passivation treatment
Colour	Black / RAL 9005 - Powder Coating
Mounting	1U 19" rackmount chassis Optional Telescopic slides
Configuration	Front I/O - Rear Power Supply
Front Panel Leds / Buttons	Power On/Off button with LED Reset button with LED
Drive Bays	1x 3.5"
Fans	6x removable PWM fans

Environmental - (Design to meet)

Operating Temperature	Standard: 0°C / +50°C Extended: -20°C / +60°C (depending on the configurations)
Operating Humidity	5% to 95% non-condensed (depending on the configurations)
Storage Temperature	-40°C / +70°C
Operating Vibration	MIL-STD-167-1A, Type I
Operating Shock	MIL-STD-810G Proc. I Method 516.7 - 15g / 11ms – half sine
Transport shock	MIL-STD-810G Proc. II Method 516.7 - 30g / 9ms sawtooth
Certifications	Directive 2014/35/UE-LVD / Directive 2014/30/UE-EMC Directive 2011/65/UE - RoHS / Regulation (EC) No 1907/2006 - REACH

GAP servers and workstations are designed in accordance with the environmental specifications indicated. Some parameters depend on the configuration. Equipment may be subjected to dedicated test profiles.