

# GAP-151R-S8-SOLO

1U Rugged Edge Server- Rear I/O & Rear Power supply  
Single Socket 5<sup>th</sup>/4<sup>th</sup> Gen Intel® Xeon® Scalable Processors



**GAP** is a product family of Rugged aluminium Servers and Workstations designed for Edge applications that require a robust MIL-GRADE certified computing platform, suitable for operations in critical environments.

1U PLATFORM	510 MM DEPTH	1 CPU	2TB RAM	UP TO 9 HOT SWAP SSD	3 I/O BOARDS
----------------	-----------------	----------	------------	-------------------------	-----------------

GAP-151R-S8-SOLO Rugged Edge Servers are powered by single-socket 5<sup>th</sup> Gen Intel® Xeon® / 4<sup>th</sup> Gen Intel® Xeon® Scalable Processors renowned for their robust architecture with enhanced AI acceleration and advanced security capabilities. Offering improved performance and efficiency, these servers are tailored to meet the demanding requirements of modern computing environments at the Edge.

The integrated IPMI services support monitoring, control, and management functions, sending alarm notifications in case of critical events.

GAP-151R-S8-SOLO are designed for 19" rackmounting and have a 1U chassis with a total overall depth of 540mm. Notably, the 19" front brackets of the chassis are strategically positioned in a backward orientation, reducing the required cabinet space to just 510mm once fully installed.

The rear I/O and rear power supply configuration offers versatile storage options, including an on board M.2 NVMe SSD and either up to three removable 2.5" SAS SSD, six removable U.2 NVMe SSD or up to nine removable 2.5" SATA SSDs.

Moreover, this rugged server can accommodate up to two full-height full-length PCIe cards, in addition to one low-profile card.

For enhanced protection against shocks and vibrations, additional boards can be supplied with a dedicated retainer kit, ensuring optimal safety even during transport.

Built to meet MIL-STD-810F standards for temperature and shock resistance, as well as MIL-STD-167-1A standards for vibration tolerance, GAP Rugged Edge Servers ensure reliable operation under the challenging conditions often found at the Edge. Additionally, they can optionally be configured to comply with MIL-STD-461 standards for EMI/EMC, featuring MIL-grade connectors for either the power input or both the I/O connectors and power supply inputs.

All units are shipped with an inventory list to guarantee configuration control and reproducibility over time. Additionally, upon request, all server configurations can undergo specific thermal or mechanical environmental stress tests.

# Technical Specifications



## System

<b>CPU</b>	5 <sup>th</sup> Gen Intel® Xeon® / 4 <sup>th</sup> Gen Intel® Xeon® Scalable processors, Single Socket LGA-4677 (Socket E) supported, CPU TDP Up to 205W TDP
<b>Memory</b>	Up to 2TB ECC RDIMM, DDR5-4800MT/s in 8 DIMM slots
<b>Chipset</b>	Intel® C741
<b>Graphics</b>	1 Aspeed AST2600 BMC port
<b>Network Connectivity</b>	1x Dedicated IPMI LAN port 2x 10GbE with RJ45 connectors
<b>Storage</b>	On Board: 1x M.2 NVMe; M-Key, 2280/22110 2x SATA Disk on Module  Removable: Up to 3x 2.5" SAS SSD or Up to 6x U.2 NVMe SSD or Up to 9x 2.5" SATA SSD
<b>TPM</b>	1x TPM Header
<b>Motherboard I/O shield</b>	1x VGA, 2x USB 3.0, 2x USB 2.0, 2x 10GbE, 1x IPMI, 1x COM (available on the rear panel)
<b>Expansion slots</b>	2x PCIe 5.0 x16 slot FHFL 1x PCIe 5.0 x16 slot low profile
<b>Operative Systems</b>	Windows® 11 IoT Enterprise, Windows® 10 IoT Enterprise LTSC, Windows® Server 2022, Windows® Server 2019, Linux
<b>IPMI</b>	IPMI2.0, SPM, Watchdog; SNMP and e-mail alarms and notifications
<b>Remote Monitoring</b>	Monitoring, control and management functions (fan speed, temperature, voltage, redundant power failure, power consumption, disk health, RAID health, and memory health)
<b>Power Supply</b>	AC or DC Redundant Power Supply - Optional AC Single

## Mechanical

<b>Dimensions</b>	483 x 44 x 510 mm 540 mm full depth (W x H x D)
<b>Material</b>	Aluminum with surface passivation treatment
<b>Colour</b>	Black / RAL 9005 - Powder Coating
<b>Mounting</b>	1U 19" rackmount chassis Optional Telescopic slides
<b>Configuration</b>	Rear I/O - Rear Power Supply
<b>Front Panel Leds / Buttons / Connectors</b>	Power On/Off button with LED Reset button with LED 2x USB 3.0
<b>Fans</b>	6x internal PWM fans

## Environmental - (Design to meet)

<b>Operating Temperatures</b>	0°C to +50°C MIL-STD-810H, Method 501.7 & 502.7 -20°C to +60°C (depending on configuration)
<b>Storage Temperature</b>	-40°C to +70°C MIL-STD-810H, Method 501.7 & 502.7
<b>Humidity</b>	5% – 95% non-condensing MIL-STD-810H 507.6
<b>Operating Vibrations</b>	MIL-STD-167-1A, Type I
<b>Not Operating Vibrations</b>	1.17 Grms, 5-500 Hz MIL-STD-810H, Method 514.8
<b>Operating Shocks</b>	20g / 11ms – half sine MIL-STD-810G, Method 516.7
<b>EMC</b>	Directive 2014/35/UE-LVD   Directive 2014/30/UE-EMC   Directive 2011/65/UE - RoHS Regulation EC No 1907/2006   MIL-STD-461G (on request)

GAP servers and workstations are designed in accordance with the environmental specifications indicated. Some parameters depend on the configuration. Equipment may be subjected to dedicated test profiles.