


# GAP-151R - G6 Series 1U RUGGED WORKSTATION



Intel® Xeon® E3-1200 v5/v6, 6th/7th Gen. Intel® Core™ i3 series - Kaby Lake / Sky Lake  
Rear I/O - Rear Power Supply



**GAP** is a line of rugged servers and workstations with an aluminum construction, designed for applications that require robust and qualified MIL-GRADE equipment, suitable for operations in critical environments.

GAP-151R G6 workstations feature a single socket Intel® Xeon® E3-1200 v5/v6, 6th/7th Gen. Intel® Core™ i3 series (Kaby Lake / Sky Lake) processors supporting up to 4 Cores (8 thread with Hyper-Threading), 8MB Smart Cache, up to 64GB DDR4 memory with our without ECC and up to 16 PCIe 3.0 lanes. The integrated IPMI services support monitoring, control, and management functions sending alarm notifications in case of critical events.

GAP-151R are designed for 19" rackmounting and have a 1U chassis with 510mm depth.

The rear I/O and rear power supply layout includes three removable SSDs, an internal SSD and an optional slim DVD. GAP-151R rugged workstations can host up to two PCIe cards.

In case additional boards are needed they can be provided with dedicated fixings for an optimal protection against shocks and vibrations also during transport.

GAP workstations are designed to meet MIL-STD-810F for temperature and shocks, MIL-STD-167-1A for vibrations. Optionally, they can conform to MIL-STD-461 for EMI /EMC.

The I/O connectors and the power supply input can be provided with MIL-GRADE connectors upon request.

All units are delivered with their inventory list to ensure configuration control and reproducibility over time. Upon request, all server configurations can run specific thermal or mechanical environmental stress test.

## FEATURES

- 1U Rugged Workstation - 510mm depth
- Intel® Xeon® E3-1200 v5/v6 series
- 6th/7th Gen. Intel® Core™ i3 series
- Rear I/O connectors
- Rear Power Input
- Redundant AC or DC Power Supply
- Up to 6 x removable 2.5" SSD + 1 x internal 2.5" SSD
- Optional DVD
- Up to 2 PCIe boards
- Optional Conformal Coating
- MIL-STD-810G
- Optional MIL-STD-461

## Technical Specifications

### System

|                          |  |
|--------------------------|--|
| <b>Processor</b>         | Intel® Xeon® E3-1200 v5/v6, 6th/7th Gen. Intel® Core™ i3 - single socket H4 (LGA 1151)   |
| <b>Memory</b>            | Up to 64GB ECC UDIMM, DDR4-2400MHz   |
| <b>Chipset</b>           | Intel® C236  |
| <b>Network</b>           | 2 x RJ45 Gigabit Ethernet<br>1 x RJ45 dedicated IPMI   |
| <b>Storage</b>           | 2.5" SATA Disk - RAID 0, 1, 5, 10  |
| <b>SATA</b>              | 6 SATA3 ports (6Gbps); RAID 0, 1, 5, 10  |
| <b>TPM</b>               | 1 TPM Header   |
| <b>Motherboard I/O</b>   | Available at the rear: 1 x VGA, 2 x USB 2.0, 2 x USB 3.0, 1 x COM, 2 x LAN, 1 x IPMI   |
| <b>Expansion slots</b>   | 2x PCIe - Bracket Full Height  |
| <b>Operative Systems</b> | Windows® 7, Windows® 8.1, Windows® 10 IoT Enterprise 2016, Windows® Server 2008 R2, Windows® Server 2012 R2, Hyper-V Server 2012 R2, Linux                               |
| <b>IPMI</b>              | IPMI2.0, SPM, Watchdog; SNMP and e-mail alarms and notifications   |
| <b>Monitoring</b>        | Monitoring, control, and management functions (fan speed, temperature, voltage, redundant power failure, power consumption, disk health, raid health, and memory health) |

### Power Supply

|                     |   |
|---------------------|---|
| <b>Power Supply</b> | 100/240 Single or Redundant VAC<br>18-36 Single or Redundant VDC<br>36-72 Single or Redundant VDC |
|---------------------|---|

### Mechanical

|                      |  |
|----------------------|--|
| <b>Dimensions</b>    | 483 x 44,45 x 510 mm from angle 19° - 540 mm full depth                              |
| <b>Construction</b>  | Aluminum with surface passivation treatment  |
| <b>Colour</b>        | Silver / RAL9007   |
| <b>Mounting</b>      | 1U 19" rackmount chassis<br>Optional telescopic slides                               |
| <b>Configuration</b> | Rear I/O and Power Supply  |
| <b>Front Panel</b>   | Led Power ON and HDD/SSD functionality; Power ON / OFF and System Reset; 2 x USB 2.0 |
| <b>Drive Bay</b>     | 1 x slim 5.25"; 2 x 3.5" bay + 1 x internal ODD 2.5"                                 |

### Environmental - (Design to meet)

|                                 |   |
|---------------------------------|---|
| <b>Operating Temperatures</b>   | 0°C to +50°C<br>MIL-STD-810H, Method 501.7 & 502.7<br>-20°C to +60°C (depending on configuration)   |
| <b>Storage Temperature</b>      | -40°C to +70°C<br>MIL-STD-810H, Method 501.7 & 502.7  |
| <b>Humidity</b>                 | 5% - 95% non-condensing<br>MIL-STD-810H 507.6   |
| <b>Operating Vibrations</b>     | MIL-STD-167-1A, Type I  |
| <b>Not Operating Vibrations</b> | 1.17 Grms, 5-500 Hz<br>MIL-STD-810H, Method 514.8   |
| <b>Operating Shocks</b>         | 20g / 11ms - half sine<br>MIL-STD-810G, Method 516.7  |
| <b>EMC</b>                      | Directive 2014/35/UE-LVD   Directive 2014/30/UE-EMC   Directive 2011/65/UE - RoHS<br>Regulation EC No 1907/2006   MIL-STD-461G (on request) |

GAP servers and workstations are designed in accordance with the environmental specifications indicated. Some parameters depend on the configuration. Equipment may be subjected to dedicated test profiles.