



# **XRS 2U S7 SERIES**

---

EXTREME RUGGED SERVERS

# XRS 2U S7 Series

## EXTREME RUGGED SERVERS



XRS Series is a product family of Extreme Rugged Servers that distinguish themselves for the superior robustness and the high performance computing technology. XRS Series Rugged Servers are designed for applications that require a MIL-grade qualified equipment, suitable for operations in very critical environment.







The XRS 2U S7 Series features a powerful single or dual socket 3<sup>rd</sup> Gen Intel® Xeon® Platform suitable for the most intense workloads and supporting a generous number of PCIe 4.0 lanes available as PCIe, M.2 and NVME slots. The integrated IPMI services support monitoring, control, and management functions sending alarm notifications in case of critical events.

The XRS S7 Series Extreme Rugged Servers has a 2U milled aluminum chassis designed to provide for superior resistance and torsional strength. The XRS 2U S7 Series has a reduced 450mm depth in the version with standard I/O connectors and a 475mm depth when equipped with round MIL-grade connectors for the I/O ports and the power input. The XRS 2U S7 Rugged Servers can host up to four low profile PCIe boards including GPU, FPGA modules and any other powerful PCI Express board. The front panel is provided with air filters and consists of two horizontal doors with thumbscrew to protect the access to the removable drives, to the USB connectors and to the power button. Optionally a key lock closing can be mounted. XRS 2U S7 Series comes with three 3.5" drive bays that can host up to nine removable SSDs.

XRS Series Extreme Rugged Servers are qualified according to MIL-STD-810G for temperature, shocks and vibrations, and conforms to MIL-STD-461 for EMI/EMC. Specific customer's configurations can be delivered fully integrated and tested.



### Product Features

-  High Performance Dual Processors Architecture
-  IPMI Based Management
-  Extreme Rugged Aluminum Chassis
-  Up to 9x SSD Drives
-  Optional round MIL connectors
-  MIL Grade Qualifications

### Technical Specifications

System	
CPU	3 <sup>rd</sup> Gen Intel® Xeon® Scalable Processors, Dual Socket LGA-4189 supported, max 270W TDP
Memory	Up to 2TB RDIMM, DDR4-3200MHz; in 8 DIMM slots
Chipset	Intel® C621A
Network Connectivity	2x RJ45 10 Gigabit Ethernet LAN ports 1x RJ45 Dedicated IPMI LAN port
Serial	1x COM port (1 header)
USB	5x USB 3.2 Gen1 ports (2 via header + 2 rear + 1 type A)
Storage	On board: 2x M.2 PCIe 4.0 x4; M.2 Form Factor: 2280/22110, 2280; M-Key 2x SATA DOM Removable: 3x 2.5" SAS SSD or 6x U.2 NVMe SATA SSD or 9x 2.5" SATA SSD
TPM	TPM Header
I/O connectors	2x 10GbE, 1x IPMI, 2x USB 3.2, VGA
Expansion slots	4x PCIe 4.0x16 low profile
Operative Systems	Windows® 10 IoT Enterprise 64bit, Windows® Server 2016 64bit; Windows® Server 2022; Windows® Server 2019 64bit; RHEL 8.4 64bit; Ubuntu 20.04.2 LTS SVR 64bit; CentOS 7.9 64bit
IPMI	IPMI2.0, SPM, Watchdog; SNMP and e-mail alarms and notifications
Remote Monitoring	Monitoring, control and management functions (fan speed, temperature, voltage, redundant power failure, power consumption, disk health, raid health, and memory health)
Power Section	
Power Input	AC or DC input, redundant PSU. Optional EMC Filter and MIL D38999 connector with single power supplies Standard rear I/O and MIL grade power input stay in 450mm depth
Mechanical	
Dimensions (W x D x H)	Width 483mm Depth 450mm - standard I/O ports and industrial / MIL grade power input Depth 475mm - MIL grade connectors Height 88mm - 2U rack
Material	Milled Aluminum chassis with surface passivation treatment; AISI316 Stainless steel rear panel
Weight	<= 15 Kg (depending on configuration)
Colour	Black / RAL 9005 - Powder Coatingw
Mounting	2U 19" rackmount chassis with bridge handles
Front Panel / Leds / Buttons / Connectors	IP30 double-door front panel with air filters. Optional door-less front panel Power ON with led; 2x USB 3.0; Remote Battery Holder
Rear Panel / Leds / Buttons / Connectors	Standard I/O connectors: 450mm depth Optional D38999 MIL type connectors on I/O and Power Input: 475mm depth
Environmental - (Design to meet)	
Operating Temperature	Standard: -5°C to +55°C according to MIL-STD-810G Change 1 (501.6 & 502.6). Extended: -20°C to +60°C (depending on configuration)
Storage Temperature	-40°C to +71°C according to MIL-STD-810G Change 1 (501.6 & 502.6)
Humidity	5% to 95% non-condensed according to MIL-STD-810G Change 1 (506.7 Procedure II)
Fungus	Conformal coating on request
Shock	40g, 11ms functional shock on each direction, according to MIL-STD-810G Change 1 (516.7 Procedure I)
Vibrations	Functional : MIL-STD-810G Change 1 (514.7, Category 20 Procedure I - Wheeled vehicle) Transportation: MIL-STD-810G Change 1 (514.7, Category 7 Procedure I - General exposure)
EMC / Electromagnetic Compatibility	According to MIL-STD-461G with EMI Filter and MIL type connectors



**GOMA ELETTRONICA SpA**

Strada Antica di Collegno, 225  
10146 Torino - Italia

Tel: +39 011 7725024

[www.gomarugged.com](http://www.gomarugged.com)

All trademarks are the property of their respective owners  
GOMA ELETTRONICA SpA • XRS2US71223

Designed by GOMA ELETTRONICA SpA



KEEP IN TOUCH

